

SILICONE & BUTYL SEALANTS

502-C NuFlex General Purpose Silicone Sealant

NuFlex general purpose silicone sealant is a one component caulking material for bonding and sealing applications plus formed in place gasketing. Adheres and bonds well to clean glass, metal, most types of wood, silicone resin, vulcanized silicone rubber, ceramic, natural and synthetic fibre, painted surfaces and many plastics. Offers outstanding resistance to weathering, vibration, moisture, ozone and both extreme high and low temperature ranges. Conforms to ASTM C920. After fully cured and washed, colours of clear, black, white and aluminum meet FDA regulation 21 CFR 177.2600 subject to end use. Product is USDA accepted for clear, black, white and aluminum colours. MSDS available upon request. Packed in cases of 12 x 10.1 oz / 300 mL plastic cartridges with removable / resealable spout.

| | |
|---------------------|---------------|
| Product # R20502CAL | Aluminum Grey |
| Product # R20502CBK | Black |
| Product # R20502CCL | Clear |
| Product # R20502CWH | White |



**** Many Other Colours Are Available For Special Order. Please Contact Your Pomar Representative With Your Requirements. ****

52-AC Manus-Bond Butyl Acoustical Sealant

Non drying synthetic rubber based sealant and bedding compound for reducing sound and vapor transmission in partition systems. Forms a long lasting and acoustical flexible seal and is paintable. Conforms to CAN/CGSB 19.21 M87. MSDS available upon request. Packed in cases of 36 x 10.3 oz / 305 mL spouted cartridges. **** Sold In Case Lots Only ****

| | |
|---------------------|---------------|
| Product # R2052ACGY | Aluminum Grey |
| Product # R2052ACBK | Black |



501-A Manus-Bond Premium Butyl Sealant

General purpose butyl sealant offers excellent adhesion and gunability to a number of substrates including aluminum, steel, wood, glass, plastics and cement. This product offers superior weather resistance and sealing properties and retains its flexibility for many years. Cleans up with mineral spirits. May be painted with most paints after full product cure 7-10 days at 72 degrees F. Stocked in cartridges but bulk product can be special ordered in 5 and 55 US gallon quantities. MSDS available upon request. Packed in cases of 36 x 325 mL spouted cartridges.

| | |
|---------------------|---------------|
| Product # R20501ABK | Black |
| Product # R20501AGY | Aluminum Grey |
| Product # R20501AWH | White |



1101-D NuFlex Butyl Sealant

Fast skinning synthetic rubber butyl sealant architectural grade offers good adhesion to most surfaces and is commonly used to seal joints between panels. Product stays flexible and serviceable down to -30 degrees Celsius. Dries by solvent evaporation and does not require painting. Can be applied to joints up to .25" wide without backer rod support. Cleans up with mineral spirits. MSDS available upon request.

| | |
|----------------------|---|
| Product # R201101DGY | Aluminum Grey: Packed in 12 x 300 mL Cartridges/Case |
|----------------------|---|

