

HEAT SHRINKABLE PRODUCTS

Thin Wall 2:1 Shrink

Black thin wall polyolefin 2:1 flexible general purpose 'HST' series economy heat shrink tube. Rated for up to 135°C continuous operation. Meets military spec # MIL-I-23053/5 Class 1 & 2, CSA # 38227, CSA certified to 600 volts at 125°C.

**** Sold By The Full Roll Quantity. Red And Clear Are Available On Special Order. ****

Product #	Nominal	Inside ID As Supplied	Inside ID After Recovery	FT/Roll
E79HST125BK	1/8"	.125"	.062"	100 FT
E79HST187BK	3/16"	.187"	.093"	100 FT
E79HST250BK	1/4"	.250"	.125"	100 FT
E79HST375BK	3/8"	.375"	.187"	100 FT
E79HST500BK	1/2"	.500"	.250"	100 FT
E79HST750BK	3/4"	.750"	.375"	50 FT
E79HST100BK	1"	1"	.500"	50 FT
E79HST150BK	1-1/2"	1.5"	.750"	50 FT
E79HST200BK	2"	2"	1"	50 FT



Dual Wall 3:1 Shrink

Black dual wall semi rigid polyolefin lined with thermoplastic adhesive 3:1 shrink rate. 'RHST' series tube offers excellent adhesion and protective qualities for electronic components, splices, etc. for industrial, vehicular and marine applications. Available in pre-cut 6" lengths or 48" sticks. Rated for up to 110°C continuous operation. Adhesive reflow will occur at temperatures above 80°C. Meets military spec # MIL-DTL-23053/4 Class 3 and UL # E-157227.

**** Red Available By Order In 1/2", 3/4" And 1" Nominal Sizes Only. Minimum May Apply. ****

Nominal	Inside ID As Supplied	Inside ID After Recovery	6" Piece Product #	48" Stick Product #
1/8"	.125"	.040"	E79RHST8BK	E79RHST8FL
3/16"	.187"	.062"	E79RHST3BK	E79RHST3FL
1/4"	.250"	.080"	E79RHST4BK	E79RHST4FL
3/8"	.375"	.120"	E79RHST6BK	E79RHST6FL
1/2"	.500"	.160"	E79RHST5BK	E79RHST5FL
3/4"	.750"	.250"	E79RHST7BK	E79RHST7FL
1"	1"	.320"	E79RHST1BK	E79RHST1FL
1-1/2"	1.5"	.510"	---	E79RHST9FL



Tech-Melt Dual Wall 4:1 Shrink

Black dual wall semi rigid polyolefin lined with thermoplastic adhesive 4:1 shrink rate. 'THST' series tube offers excellent adhesion and offers a waterproof seal. Sized with universal industry code and tubing is stencil marked for easy identification. Operating temperature from -55°C to 125°C. Excellent insulator and protector for industrial, vehicular and marine applications. Sold in 6" pieces.

Product #	Size	Expanded ID	Package Quantity
E79THST1BK	# 1	.228"	50
E79THST2BK	# 2	.299"	50
E79THST3BK	# 3	.435"	50
E79THST4BK	# 4	.704"	25

