

SWITCHING DEVICES

Universal Head Lamp Switch

Three position headlamp switch (off-park & tail-head & tail). Black knob 'lights' imprint. Mounting stem 7/16-28 thread. Four screw terminals.

Product # E757124



Wiper System Switches

Product # X75SW13984 Two Speed Single Wiper Motor Control Switch *Without* Wash Feature For 12 Volt DC Systems Without Dynamic Park. Features 3 Positions: Off/Park - Low - High. Black Plastic Knob Secured With Set Screw "Wiper" Imprint & Mounting Stem 7/16-28 Thread x .38" Long. Four Blade Terminals.

Product # X75SW48640 Two Speed Dual Wiper Motor Control Switch *With* Push-To-Wash Feature To Activate Washer Pump For 12 Volt DC Systems Without Dynamic Park. Features 3 Positions: Off/Park - Low - High. Black Plastic Knob Secured With Set Screw "Wiper Washer" Imprint & Mounting Stem 7/16-28 Thread x .38" Long. Seven Blade Terminals.



**** Pomar Is Able To Supply Wiper Systems Designed For Specific Applications. In Addition, Replacement Parts For Johnson Electric (Former United Technologies), Robert Bosch & Sprague Devices Are Available. Please Contact Our Sales Department With Your Requirements. ****

Door & Momentary Switches

Product # E759002 SPST - Normally Off - On With Plunger Depressed - Spring Return To Off. Two Screw Terminals, Mtg Holes On 1-3/8" Centers, Plunger 7/16" Long.

Product # E759245 Momentary Extra Heavy Duty Push Button Switch Off-On, Normally Off. On When Button Depressed, Spring Return To Off. Includes Snap In Place Protective Rubber Cap. Two Screw Terminals.

Product # E759001 SPST - Normally On - Off With Plunger Depressed - Spring Return To On. Two Screw Terminals, Mtg Holes On 1-3/8" Centers, Plunger 7/16" Long.

Product # E759055 SPST - Normally On - Off With Plunger Depressed - Spring Return To On. Plated Steel Case, Two Flats On Stem For Mounting In Double D Shape Hole, 1/2" Long Plunger - Mounting Stem 7/16-20 Thread x 7/16" Long - Two Screw Terminals.

E759001 & E759002



E759055



E759245

Single Pole Master Disconnect Switch With Plated Steel Case

Master disconnect switch single pole two position Off-On rated for 6 to 36 volt DC systems. Copper contacts UL listed 375M power switch. Two 3/8-24 stud terminals with brass mounting stem 3/4-16 diameter x 23/32" long. Fits panels up to 3/16" thick. **** Rated 175 Amps Continuous, 1000 Amps Intermittent, 15 Seconds On, 5 Minutes Off ****

Product # E752484



SWITCHING DEVICES

Single Pole Master Disconnect Switch With Brass Case

Master disconnect switch single pole two position off-on rated for 6 to 36 volt DC systems. Weather resistant switch with O-ring seal in operating shaft and gasket sealed terminal insulator and brass case. Two 3/8-24 stud terminals, long style brass mounting stem 3/4-16 diameter x 1-13/32" long. Fits panels up to 15/16" thick. **** Rated 175 Amps Continuous, 1000 Amps Intermittent, 15 Seconds On, 5 Minutes Off ****

Product # E75248402



Master Disconnect Switch Face Plate

Face plate for single pole two position master disconnect switches with "On - Off" imprinted.

Product # E7582065



Dual Battery Selector & Master Disconnect Switch

Allows control of dual battery installations for power management. Four positions: Off-On - battery # 1 - on both batteries - on battery # 2. UL listed 707B rated as 310 amps continuous, 500 amps intermittent at 6 to 36 volts DC. Heavy duty vapor proof and weather, dust and corrosion resistant construction. Three 3/8-24 copper stud terminals with brass hex nuts. Can be surface or flush mounted. Overall 6" diameter flange with 2-5/8" height. Wiring instructions included.

Product # E75M750




Ignition Switches

Product # E759564304 Heavy Duty Coded Tumbler Lock With Two Keys, 4-Position Ignition/Starter Switch With Spring Return To IGN/ACC Position. Key Only Removable In Off Position. Diecast Housing With 4 Screw Terminals. Mounting Bushing 3/4-24 And Fits Panels .060" To .110" Thickness. Rated At 12 Volts DC: 10 Amp Accessory, 10 Amp Ignition & 5 Amp Start. **** Versions Which Accept Delphi/Packard Connector # 2962912 Or Equivalent Also Available. Please Contact Us With Your Requirements. ****

Product # E759579 Heavy Duty Universal Coded Tumbler Lock With Two Keys, 4-Position Ignition/Starter Switch With Spring Return To IGN/ACC Position. Key Only Removable In Off Position. Diecast Housing With 4 Screw Terminals. Mounting Bushing 3/4-20 And Fits Panels Up To 3/8" Thickness. Rated At 12 Volts DC: 10 Amp Accessory, 10 Amp Ignition & 5 Amp Start.

E759564304



E759579

**** We Also Offer Universal Switches Of 2 Or 3 Positions As Well As Marine And Sealed Ignition Switches. Please Contact Our Sales Department With Your Requirements. ****